



Seisuga 1.November 2005

Soovituslik Jaehinnakiri 2005
Kõik hinnad sisaldavad käibemaksu 18%

SSA-JS2080B 2/1 CHANNEL POWER AMPLIFIER
2x95W RMS,1x260W RMS @4 ohm **1850.-**
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 1 x 30A fuse.

SSA-JS4080B 4/3/2 CHANNEL POWER AMPLIFIER
4x80W RMS,2x200W RMS @4 ohm **2500.-**
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 2 x 30A fuse.

SSA- 4100 4/3/2 CHANNEL POWER AMPLIFIER
4x80W RMS,2x200W RMS @4 ohm **2500.-**
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 2 x 30A fuse.

SSA - D4150 4/3/2 CHANNEL POWER AMPLIFIER
4x105W RMS,2x272W RMS @4 ohm **4500.-**
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 1 x 60A fuse.

SSA - D5450 5/4/3 CHANNEL POWER AMPLIFIER
4x50+182W RMS,2x130+145W RMS@4 ohm **4950.-**
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 1 x 60A fuse.

SSA - D1450 MONOBLOCK DIGITAL POWER AMPLIFIER
1 x 550W RMS@4 ohm,1x812W RMS@2 ohm **5750.-**
HP/LP crossover.Bass Booster. 1 ohm operation.Thermal,Speaker overload protection. 1 x 80A fuse.

SSA-G75.2 2/1 CHANNEL POWER AMPLIFIER
2x100W RMS @4ohm.2x153W RMS @2 ohm **2150.-**
Low Pass Filter.High Pass Filter.Subsonic Filter.Bass EQ.Line OUT. DC 12V...18V. 2 x 25A fuse.

SSA-G350.2 2/1 CHANNEL POWER AMPLIFIER
2x264W RMS @4ohm.2x403W RMS @2 ohm **3750.-**
Low Pass Filter.High Pass Filter.Subsonic Filter.Bass EQ.Line OUT.Remote Control. DC 12V...18V. 3x30A fuse.

SSA- G1200.1 MONOBLOCK DIGITAL AMPLIFIER
390W RMS@4ohm.640W RMS@2ohm.870W RMS 1ohm **5200.-**
Low Pass Filter.Subsonic Filter.Bass EQ.Line OUT.Remote Control. DC 12V...18V. 3x30A fuse.

SSA-854 4/3/2 CHANNEL POWER AMPLIFIER
4x70W RMS @4ohm.2x175W RMS @4 ohm **2400.-**
2*Low Pass Filter.2*High Pass Filter.2*Bass Boost. DC 12V 2 x 30A fuse.

SSA- D7000 MONOBLOCK DIGITAL AMPLIFIER
1200W RMS@4 ohm.2400W RMS@2 ohm.3500W RMS 1 ohm
Variable Subsonic Filter.Variable Bass EQ.Variable Phase Shift.Remote Bass control.



16500.-

SSA - 3000	4 BAND GRAPHIC EQUALISER Pre amp.Aux input.10Hz..50KHz.BassEQ 55Hz,MidBassEQ200Hz. Mid.EQ 2,5KHz,High EQ 20KHz.Subwoofer Freq.range 30Hz...120Hz.	975.-
SSA - 2800	2 WAY ELECTRONIC X - OVER HP x over freq.32Hz..400Hz.Subwoofer 32Hz...400Hz.	850.-
SSA - 2900	3 WAY ELECTRONIC X - OVER HP x over freq.32Hz..400Hz.Subwoofer 32Hz...400Hz.	1190.-
SSW - 2000	8" (20 cm) SUBWOOFER 4 ohm 100W RMS 200W max. 45Hz....1500Hz Sensitivity 87 dB Chrome cone.Butyl Rubber Edge.Kapton voice coil.Gold Push Terminals.	495.-
SSW - 2500	10" (25 cm) SUBWOOFER 4 ohm 200W RMS 400W max. 35Hz....1000Hz Sensitivity 87 dB Chrome cone.Butyl Rubber Edge.Kapton voice coil.Gold Push Terminals.	610.-
SSW - 3000	12" (30 cm) SUBWOOFER 4 ohm 250W RMS 500W max. 30Hz....900Hz Sensitivity 88 dB Chrome cone.Butyl Rubber Edge.Kapton voice coil.Gold Push Terminals.	620.-
SSW - 3800	15" (38 cm) SUBWOOFER 4 ohm 300W RMS 600W max. 26Hz....800Hz Sensitivity 91 dB Chrome cone.Butyl Rubber Edge.Kapton voice coil.Gold Push Terminals.	790.-
SSW-351	12" (30 cm) SUBWOOFER 4 ohm 380W RMS 800W max.Sensitivity 94db/SPL Treated cellulose cone.Carbonfiber dust cap.Rubber magnet boot.	1100.-
SSW-351DVC	12" (30 cm) SUBWOOFER 2 x 4 ohm 750W RMS 1500W max.Sensitivity 89db/SPL Treated cellulose cone.Carbonfiber dust cap.Rubber magnet boot.	1200.-
SSW-381	15" (38 cm) SUBWOOFER 4 ohm 600W RMS 1200W max.Sensitivity 89db/SPL 2,5"AL bobbin single voice coil.Treated cellulose cone.Carbonfiber dust cap.Rubber magnet boot.	1300.-
SSW-381DVC	15" (38 cm) SUBWOOFER 2 x 4 ohm 1000W RMS 2000W max.Sensitivity 89db/SPL 2,5"AL bobbin dual voice coil.Treated cellulose cone.Carbonfiber dust cap.Rubber magnet boot.	1400.-
SSWD-6000	15" (38 cm) PRO SUBWOOFER 2 x 2 ohm 1500W RMS 3000W max. Anti vibration aluminium basket.Semi press cone.4 layer BASV 3" voice coil.High temperature resistant lead wire.Gold push terminals.880 oz Super magnet structure.	3900.-
SSW-10SVC	10" (25 cm) PRO SUBWOOFER 4 ohm 600W RMS 1500W max. 20Hz...400Hz Chrome cone.Butyl Rubber Edge.3" Aluminium voice coil.Silver Push Terminals.Aluminium Basket.	2050.-
SSW-12SVC	12" (30 cm) PRO SUBWOOFER 4 ohm 800W RMS 2000W max. 20Hz...400Hz Chrome cone.Butyl Rubber Edge.3" Aluminium voice coil.Silver Push Terminals.Aluminium Basket.	2200.-
SSDW-2800DVC	12" (30 cm) PRO SUBWOOFER 4 + 4 ohm 1200W RMS 2800W max. 20Hz...400Hz Chrome cone.Butyl Rubber Edge.3" Aluminium voice coil.Silver Push Terminals.Aluminium Basket.	2800.-
SSW-10DVC	10" (25 cm) PRO SUBWOOFER 4 + 4 ohm 500W RMS 1000W max. Chrome cone.Butyl Rubber Edge.3" voice coil.Push Terminals.Aluminium Basket.LED flashing light.	1550.-
SSW-12DVC	12" (30 cm) PRO SUBWOOFER 4 + 4 ohm 600W RMS 1200W max. Chrome cone.Butyl Rubber Edge.3" voice coil.Push Terminals.Aluminium Basket.LED flashing light.	1625.-



SSC - 400CK **4" (10 cm) COMPONENT 2 WAY SPEAKER** **585.-**
 75W RMS 200W max. 70Hz...20Khz. Sensitivity 89dB/W/m
 Polypropylene cone.Silk dome Neodymium Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.

SSC - 525CK **5,25" (13 cm) COMPONENT 2 WAY SPEAKER** **650.-**
 150W RMS 300W max. 65Hz...20Khz. Sensitivity 89dB/W/m
 Polypropylene cone.Silk dome Neodymium Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.

SSC - 650CK **6,5" (16 cm) COMPONENT 2 WAY SPEAKER** **750.-**
 200W RMS 400W max. 65Hz...20Khz. Sensitivity 89dB/W/m
 Polypropylene cone.Silk dome Neodymium Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.

SSC - 100CK **4" (10 cm) COMPONENT 2 WAY SPEAKER** **1350.-**
 100W RMS 200W max. 90Hz...22Khz. Sensitivity 91dB/W/m
 Polypropylene cone.Silk dome Neodymium Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.

SSC - 130CK **5,25" (13 cm) COMPONENT 2 WAY SPEAKER** **1450.-**
 200W RMS 400W max. 70Hz...32Khz. Sensitivity 91dB/W/m
 Polypropylene cone.1" Neodymium Titanium cone Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.

SSC - 165CK **6,5" (16 cm) COMPONENT 2 WAY SPEAKER** **1650.-**
 300W RMS 500W max. 63Hz...32Khz. Sensitivity 91dB/W/m
 Polypropylene cone.1" Neodymium Titanium cone Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.



SS-S142 **4" (10 cm) COAXIAL 2 WAY SPEAKER** **295.-**
 35W RMS 130W max. 65Hz....20KHz Sensitivity 88 dB
 29mm soft-dome tweeter.NdFeB magnet.

SS-S152 **5,25" (13 cm) COAXIAL 2 WAY SPEAKER** **390.-**
 40W RMS 150W max. 55Hz....20KHz Sensitivity 89 dB
 29mm soft-dome tweeter.NdFeB magnet.

SS-S162 **6" (16 cm) COAXIAL 2 WAY SPEAKER** **450.-**
 50W RMS 200W max. 45Hz....22KHz Sensitivity 90 dB
 38mm mylar dome tweeter.Neodymium magnet.

SS-S692 **6"x 9" (15 x 23cm) COAXIAL 2 WAY SPEAKER** **620.-**
 80W RMS 450W max. 35Hz....22KHz Sensitivity 91 dB
 38mm Mylar dome tweeter.

SS-S694 **6"x 9" (15 x 23cm) COAXIAL 4 WAY SPEAKER** **685.-**
 80W RMS 500W max. 35Hz....22KHz Sensitivity 91dB
 38mm Mylar dome tweeter.27mm piezo tweeter x2



SS-S1045 **4" (10 cm) COAXIAL 2 WAY SPEAKER** **295.-**
 35W RMS 110W max. 100Hz....20KHz Sensitivity 89 dB
 Titanium plated Injected Cone.Butyl rubber Edge.

SS-S1345 **5,25" (13 cm) COAXIAL 2 WAY SPEAKER** **390.-**
 40W RMS 150W max. 50Hz....20KHz Sensitivity 89 dB
 Titanium plated Injected Cone.Butyl rubber Edge.

SS-S1655 **6,5" (16 cm) COAXIAL 3 WAY SPEAKER** **455.-**
 40W RMS 180W max. 60Hz....20KHz Sensitivity 90 dB
 Titanium plated Injected Cone.Butyl rubber Edge.

SS-S6957 **6"x 9" (15 x 23cm) COAXIAL 3 WAY SPEAKER** **620.-**
 60W RMS 260W max. 40Hz....20KHz Sensitivity 91 dB
 Titanium plated Injected Cone.Butyl rubber Edge.

SS-S6977 **6"x 9" (15 x 23cm) COAXIAL 4 WAY SPEAKER** **685.-**
 80W RMS 300W max. 40Hz....20KHz Sensitivity 90dB
 Titanium plated Injected Cone.Butyl rubber Edge.



CP - 10D**1 FARAD CAPACITOR**
With DISPLAY and remote.**1500.-****SSMSU 200 R**

RADIO,CD,MP3,USB stick,SD memory card HEAD UNIT

2750.-**SSMSU 200R**

Power supply: 12V DC(11v-16V)
 Test voltage: 14.4V. negative ground
 Maximum power output: 45W X 4 channels
 Suitable speaker impedance: 4-8 ohm
 Suitable speaker power: 80-100W x 4 channels
 Pre-Amp output voltage: 4.0V
 Fuse: 15Amp
 Dimensions(WxHxD): 178x50x163mm
 Weight 1.64Kg
 Aux-Is oval: >330 mm
 Subwoofer output voltage: 4.0 V
FM Stereo Radio
 Frequency range: 87.5 -108.0 MHz
 Sensitivity: 10dB
 Frequency response: 30Hz-15KHz
 Stereo separation: 30dB(1KHz)
 Image response ratio: 50dB
 IF response ratio: 70dB
 Signal/noise ratio 55dB
MW Radio
 Frequency range: 522-1620KHz
 Sensitivity(S/N=20dB): 30 dB
Disc Player

**2500.-****RTC-DVD101****RO-TECH car DVD player**

Disc formats supported by this player:
 DVD 12cm disc (single sided disc only)
 VIDEO CD 12cm disc
 CD 12cm disc
 Mp3 12cm disc
 Audio Frequency response 20 Hz...20 000 Hz
 S/N ratio 90dB (JIS)
 Supply voltage DC 12V (11V...15V),test voltage 14,4V.
 Current Consumption: less than 2A

**FL 1040 IR****STARSOUND LCD-TFT Roof monitor.****3900.-**

Roofmount Matrix Active 8" TFT LCD Monitor
 Multi-System With Wide View Angle
 English Operation System Display
 High Resolution Display
 Full Function Remote Control
 Built-in Dome Lights
 PAL & NTSC
 Display ratio 4:3
 800*600 pixels
 Power supply :DC12V
 Power consumption 10W



STARSOUND TOODETE MAALETOOJA
Omitron OÜ
 80010 Pärnu , Lao 8 - 5 Tel/Fax 4478472
 www.omitron.ee info@omitron.ee