



Soovituslik Jaehinnakiri 2004  
Kõik hinnad sisaldavad käibemaksu 18%

**SSA-260** 2/1 CHANNEL POWER AMPLIFIER  
**2x60W RMS,1x120W RMS @4 ohm** **1750.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 1 x 25A fuse.

**SSA-2100** 2/1 CHANNEL POWER AMPLIFIER  
**2x100W RMS,1x200W RMS @4 ohm** **2250.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 2 x 25A fuse.

**SSA- 460** 4/3/2 CHANNEL POWER AMPLIFIER  
**4x60W RMS,2x160W RMS @4 ohm** **2550.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 2 x 25A fuse.

**SSA- 4100** 4/3/2 CHANNEL POWER AMPLIFIER  
**4x100W RMS,2x200W RMS @4 ohm** **2990.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 2 x 30A fuse.

**SSA-JS2080B** 2/1 CHANNEL POWER AMPLIFIER  
**2x80W RMS,1x250W RMS @4 ohm** **2350.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 1 x 30A fuse.

**SSA-JS4080B** 4/3/2 CHANNEL POWER AMPLIFIER  
**4x80W RMS,2x250W RMS @4 ohm** **3450.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 2 x 30A fuse.

**SSA - D2500** 2/1 CHANNEL POWER AMPLIFIER  
**2x350W RMS,1x1080W RMS @4 ohm** **7500.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 1 x 90A fuse.

**SSA - D4150** 4/3/2 CHANNEL POWER AMPLIFIER  
**4x100W RMS,2x300W RMS @4 ohm** **4900.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 1 x 60A fuse.

**SSA - D5450** 5/4/3 CHANNEL POWER AMPLIFIER  
**4x60+150W RMS,2x180+150W RMS@4 ohm** **5950.-**  
HP/LP crossover.Bass Booster. 2 ohm operation.Thermal,Speaker overload protection. 1 x 60A fuse.

**SSA - D1450** MONOBLOCK DIGITAL POWER AMPLIFIER  
**1 x 500W RMS@4 ohm,1x1000W RMS@2 ohm** **5750.-**  
HP/LP crossover.Bass Booster. 1 ohm operation.Thermal,Speaker overload protection. 1 x 80A fuse.

**SSA - 3000** 4 BAND GRAPHIC EQUALISER  
Pre amp.Aux input.10Hz..50KHz.BassEQ 55Hz,MidBassEQ200Hz.  
Mid.EQ 2,5KHz,High EQ 20KHz.Subwoofer Freq.range 30Hz...120Hz. **975.-**

**SSA - 2800** 2 WAY ELECTRONIC X - OVER  
HP x over freq.32Hz..400Hz.Subwoofer 32Hz...400Hz. **850.-**

**SSA - 2900** 3 WAY ELECTRONIC X - OVER  
HP x over freq.32Hz..400Hz.Subwoofer 32Hz...400Hz. **1190.-**



<b>SSW - 2000</b>	<b>8" ( 20 cm ) SUBWOOFER 4 ohm</b> 100W RMS 200W max. 45Hz....1500Hz Sensitivity 87 dB Chrome cone.Butyl Rubber Edge.Kapton voice coil.Gold Push Terminals.	<b>495.-</b>
<b>SSW - 2500</b>	<b>10" ( 25 cm ) SUBWOOFER 4 ohm</b> 200W RMS 400W max. 35Hz....1000Hz Sensitivity 87 dB Chrome cone.Butyl Rubber Edge.Kapton voice coil.Gold Push Terminals.	<b>610.-</b>
<b>SSW - 3000</b>	<b>12" ( 30 cm ) SUBWOOFER 4 ohm</b> 250W RMS 500W max. 30Hz....900Hz Sensitivity 88 dB Chrome cone.Butyl Rubber Edge.Kapton voice coil.Gold Push Terminals.	<b>620.-</b>
<b>SSW - 3800</b>	<b>15" ( 38 cm ) SUBWOOFER 4 ohm</b> 300W RMS 600W max. 26Hz....800Hz Sensitivity 91 dB Chrome cone.Butyl Rubber Edge.Kapton voice coil.Gold Push Terminals.	<b>790.-</b>



<b>SSW-10SVC</b>	<b>10" ( 25 cm ) PRO SUBWOOFER 4 ohm</b> 600W RMS 1500W max. 20Hz....400Hz Chrome cone.Butyl Rubber Edge.3" Aluminium voice coil.Silver Push Terminals.Aluminium Basket.	<b>2050.-</b>
<b>SSW-12SVC</b>	<b>12" ( 30 cm ) PRO SUBWOOFER 4 ohm</b> 800W RMS 2000W max. 20Hz....400Hz Chrome cone.Butyl Rubber Edge.3" Aluminium voice coil.Silver Push Terminals.Aluminium Basket.	<b>2200.-</b>
<b>SSDW-2800DVC</b>	<b>12" ( 30 cm ) PRO SUBWOOFER 4 + 4 ohm</b> 1200W RMS 2800W max. 20Hz....400Hz Chrome cone.Butyl Rubber Edge.3" Aluminium voice coil.Silver Push Terminals.Aluminium Basket.	<b>2800.-</b>



<b>SSW-10DVC</b>	<b>10" ( 25 cm ) PRO SUBWOOFER 4 + 4 ohm</b> 500W RMS 1000W max. Chrome cone.Butyl Rubber Edge.3" voice coil.Push Terminals.Aluminium Basket.LED flashing light.	<b>1550.-</b>
<b>SSW-12DVC</b>	<b>12" ( 30 cm ) PRO SUBWOOFER 4 + 4 ohm</b> 600W RMS 1200W max. Chrome cone.Butyl Rubber Edge.3" voice coil.Push Terminals.Aluminium Basket.LED flashing light.	<b>1625.-</b>



<b>SSC - 400CK</b>	<b>4" ( 10 cm ) COMPONENT 2 WAY SPEAKER</b> 75W RMS 200W max. 70Hz...20Khz. Sensitivity 89dB/W/m Polypropylene cone.Silk dome Neodymium Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.	<b>585.-</b>
<b>SSC - 525CK</b>	<b>5,25" ( 13 cm ) COMPONENT 2 WAY SPEAKER</b> 150W RMS 300W max. 65Hz...20Khz. Sensitivity 89dB/W/m Polypropylene cone.Silk dome Neodymium Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.	<b>650.-</b>
<b>SSC - 650CK</b>	<b>6,5" ( 16 cm ) COMPONENT 2 WAY SPEAKER</b> 200W RMS 400W max. 65Hz...20Khz. Sensitivity 89dB/W/m Polypropylene cone.Silk dome Neodymium Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.	<b>750.-</b>



<b>SSC - 100CK</b>	<b>4" ( 10 cm ) COMPONENT 2 WAY SPEAKER</b> 100W RMS 200W max. 90Hz...22Khz. Sensitivity 91dB/W/m Polypropylene cone.Silk dome Neodymium Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.	<b>1350.-</b>
<b>SSC - 130CK</b>	<b>5,25" ( 13 cm ) COMPONENT 2 WAY SPEAKER</b> 200W RMS 400W max. 70Hz...32Khz. Sensitivity 91dB/W/m Polypropylene cone.1" Neodymium Titanium cone Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.	<b>1450.-</b>
<b>SSC - 165CK</b>	<b>6,5" ( 16 cm ) COMPONENT 2 WAY SPEAKER</b> 300W RMS 500W max. 63Hz...32Khz. Sensitivity 91dB/W/m Polypropylene cone.1" Neodymium Titanium cone Tweeter.Butyl rubber edge.Ext.12dB/oct.Crossover.	<b>1650.-</b>



<b>SS-S1045</b>	<b>4" ( 10 cm ) COAXIAL 2 WAY SPEAKER</b> 35W RMS 110W max. 100Hz....20KHz Sensitivity 89 dB Titanium plated Injected Cone.Butyl rubber Edge.	<b>295.-</b>
<b>SS-S1345</b>	<b>5,25" ( 13 cm ) COAXIAL 2 WAY SPEAKER</b> 40W RMS 150W max. 50Hz....20KHz Sensitivity 89 dB Titanium plated Injected Cone.Butyl rubber Edge.	<b>390.-</b>
<b>SS-S1655</b>	<b>6,5" ( 16 cm ) COAXIAL 3 WAY SPEAKER</b> 40W RMS 180W max. 60Hz....20KHz Sensitivity 90 dB Titanium plated Injected Cone.Butyl rubber Edge.	<b>455.-</b>
<b>SS-S6957</b>	<b>6"x 9" ( 15 x 23cm ) COAXIAL 3 WAY SPEAKER</b> 60W RMS 260W max. 40Hz....20KHz Sensitivity 91 dB Titanium plated Injected Cone.Butyl rubber Edge.	<b>620.-</b>
<b>SS-S6977</b>	<b>6"x 9" ( 15 x 23cm ) COAXIAL 4 WAY SPEAKER</b> 80W RMS 300W max. 40Hz....20KHz Sensitivity 90dB Titanium plated Injected Cone.Butyl rubber Edge.	<b>685.-</b>
<b>CP - 10D</b>	<b>1 FARAD CAPACITOR</b> With DISPLAY and remote.	<b>1500.-</b>



Omitron

STARSOUND TOODETE MAALETOOJA  
**Omitron OÜ**  
 80010 Pärnu , Lao 8 - 5 Tel/Fax 4478472  
[www.omitron.ee](http://www.omitron.ee) [info@omitron.ee](mailto:info@omitron.ee)